

DF 545

Multi-Purpose, Industrial Grade
Double-Faced Cloth Tape

Shurtape®

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Carpet hold-down for convention trade, general purpose uses in aircraft and maintenance construction, hanging poly sheeting in mold/asbestos remediation industry and splicing applications

ADVANTAGES AND BENEFITS

- > Natural rubber/synthetic rubber blend offers excellent adhesion
- > Removes cleanly leaving no residue
- > Premium grade silicone coated release liner offers easy unwind

CONSTRUCTION

Overall Grade/Function: Multi-purpose, Industrial Grade
Backing: Polyester/cotton blend cloth
Adhesive: Synthetic/natural rubber blended adhesive
Liner: Siliconized, polyethylene release liner

COLOR(S)



Natural (NAT)



STANDARD WIDTH(S)

48 mm

STANDARD LENGTH(S)

23 m 33 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	25 lbs/in width	43.8 N/10 mm
Adhesion to Stainless Steel	45 oz/in width	4.93 N/10 mm
Thickness	15.5 mils	0.39 mm
Elongation	9 %	9 %
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

"Shurtape" is a registered trademark of Shurtape Technologies, LLC

Form# TDS-DF545-02/26/2005